

Instructions for the safe use of WINNER 200 Grade 10 chain slings

ALWAYS

- Plan a lift ensuring that the weight of the load is known, and that the capacity of the sling is sufficient, and that the mode factor has been taken into account.
- Ensure that the slings are within their inspection period.
- Inspect chain slings and accessories before use.
- Fit chain slings carefully and securely, protect them from sharp edges, and position the hooks to face outward from the load.
- Back- hook free legs on to the master link.
- Use the shortening device provided to ensure that the load is properly balanced, and will not tilt or fall.
- Ensure that the load is free to be lifted, and make a trial lift and lower.
- Keep fingers, toes etc, clear when tensioning slings and when landing loads.
- Take the load steadily avoiding shock loads.
- Store chain slings in a clean and dry environment, and inspect for damage after use.

FOR MORE DETAILED INFORMATION ON USE AND MAINTENANCE OF PEWAG CHAIN SLINGS, REFER TO THE PEWAG TECHNICAL BROCHURE

NEVER

- Use damaged chain slings or accessories.
- Twist, knot or tie chain slings.
- Attempt to shorten a chain leg other than by means of an integral-shortening device, provided for that purpose.
- Use the shortening device to form a basket loop, unless the sling has been designed for that purpose.
- Force, hammer or wedge chain slings or their fittings into position.
- Lift on the point of the hook.
- Expose chains to chemicals, particularly acids or acid fumes, without consulting the supplier.
- Use chain slings at temperatures above 200 degrees C or below -40degrees C, without consulting the supplier.
- Overload a chain sling due to the weight of the load, or the mode of use.
- Shock load a chain sling.
- Trap a chain sling when landing a load, or attempt to free a trapped chain from under a load.
- Allow personnel to ride on loads.
- Alter, modify or repair a chain sling, but refer such matters to a competent person.

Safety First Industrial Ltd.,

Unit 11 Enterprise Way, Bolt St, Newport, Gwent, NP20 2AQ Email: sales@safetyfirstind.com

Tel: 01633 842088 Fax: 0870 1349816 Mobile: 07888 730616

